

7726DA Series Premium Range Surface Mounted Door Closer



Rack and pinion adjustable power door closer suitable for architectural and commercial applications.

Specifications

Power	EN adjustable 2 to 6.
Back check (BC)	Adjustable.
Hold Open	Adjustable. Hold-open can be set at any angle up to 150° of opening.
Handing	Non-handed. Suitable for left or right hand doors.
Cover	Fully formed metal.
Materials	Extruded aluminium body manufactured from high-performance silicon alloy.
Mechanism	Rack and pinion design.
Mounting	Regular, parallel and over-door mounting.
Valves	Adjustable closing and latching speed valves with overload protection.
Delayed Action	Adjustable.

Ordering Information

Model	Part Numbers	Finishes
Standard Arm	7726DASSS	Satin Stainless Steel
	7726DAPSS	Polished Stainless Steel
	7726DASIL	Silver
Hold-Open	7726HDASSS	Satin Stainless Steel
	7726HDAPSS	Polished Stainless Steel
	7726HDASIL	Silver

Other finishes available on request

Standards and Compliance



The Lockwood 7726DA series closer has been successfully tested up to four hours (depending on type of doorset) on fire door assemblies in accordance with Australian Standard AS1905.1:2005, Part: Fire Resistant Door sets.



Note: Hold open option is not approved on any fire door.

7726DA Series Premium Range Surface Mounted Door Closer

7726DA Standard Arm

Part Numbers	Description
--------------	-------------

7726DA	Non hold-open
7726HDA	Hold-open





Closer installed on pull side of door. This mounting position permits opening of 180°.

7726DA Parallel Arm

Part Numbers	Description
--------------	-------------

7726DA	Non hold-open
7726HDA	Hold-open





Closer installed on push side of door. This mounting position permits opening of 180°.

7726DA Over Door Mounting

Part Numbers	Description
--------------	-------------

7726DA	Non hold-open
7726HDA	Hold-open



Closer installed on push side of door and top rail where conditions do not allow parallel mounting. This mounting position permits opening of 180°.